



Empty CMC72-32B Passive Venting Outdoor Battery Cabinet

The cabinet is designed to house rack mounted equipment. This cabinet provides mechanical and environmental protection for the equipment inside.

- Provides mounting space for power distribution, network servers, batteries, or other equipment.
- Front door compatible with Pad Lock.
- Provides flexible access for the cable entrances.
- Optional heater for cold environments.
- Provides space for 5 VRLA Battery Strings
- Common parts available across the same platform.

Product Classification

Product Type	Outdoor cabinet
Product Series	CMC

General Specifications

Access	Front and rear door
Alarm Type	Door alarm
Batteries	Not included
Batteries Supported	20
Capacity	1000 W Heater
Color	Gray
Cooling	Passive Cooling
Door Security	Swing handle, puck lock system for front door
Mounting	Pad
Noise Emission, maximum	65 dBA

Dimensions

72B5-P1-A00D10-00 | CMC72-32B

Height	1,828.8 mm 72 in
Width	812.8 mm 32 in
Depth	939.8 mm 37 in

Electrical Specifications

Battery String Current, maximum	200 A-h @ -48 Vdc
Battery Strings, quantity	5 @ -48 Vdc
Voltage	-48 Vdc

Material Specifications

Finish	Powder coated UV resistant
Material Type	Aluminum

Environmental Specifications

Operating Temperature	-40 °C to +46 °C (-40 °F to +115 °F)
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Environmental Space	UV resistant for outdoor
Qualification Standards	IP55 Telcordia GR-487
Thermal Compliance	GR-487