

F4-CLAMP-E3B



KwikClamp™ Hanger for 1/2 in superflexible coaxial cable, triple stack; includes hardware

Product Classification

Product Type	Hanger kit
Product Brand	KwikClamp™
Ordering Note	ANDREW® standard product in Europe, the Middle East, and Africa Minimum order quantity (MOQ) is 1 box

General Specifications

Cables per Hanger	3
Color	Black
Hanger Type	KwikClamp™ hanger
Mounting	3–25 mm angle iron 3–25 mm flat plate Round Member 8–25 mm

Dimensions

Height	165 mm 6.496 in
Width	31 mm 1.22 in
Length	42 mm 1.654 in
Compatible Diameter, maximum	14 mm 0.551 in
Compatible Diameter, minimum	13 mm 0.512 in
Nominal Size	1/2 in
Hanger Spacing, maximum	1.83 m 6.004 ft

Electrical Specifications

Return Loss Effect, maximum	0.1 dB
DTF Effect, maximum	0.1 dB

Material Specifications

Material Type	Engineered plastic Stainless steel
---------------	--------------------------------------

F4-CLAMP-E3B

Mechanical Specifications

Vibration Survival	≥4 hours at resonant frequency
---------------------------	--------------------------------

Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Corrosion Resistance, minimum with no degradation	≥500 hours in salt spray chamber
Environmental Strength Capability	Five times cable weight
UV Resistance, minimum with no degradation	≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

Height, packed	15.5 cm 6.102 in
Width, packed	30.5 cm 12.008 in
Length, packed	35.5 cm 13.976 in
Included	Hardware
Packaging quantity	48
Weight, gross	8 kg 17.637 lb