PB-G3T-2



Tapered Pipe Frame Stand-Off Bracket, 36 in, for 2 in to 5 in OD legs

Product Classification

Product Type Stand-off mount

Ordering Note ANDREW® standard product in the United States and Canada

Warranty One year

General Specifications

Mounting Legs, 50.8–127 mm (2–5 in) OD

Tower Taper Tapered

Dimensions

 Height
 1,447.8 mm | 57 in

 Width
 254 mm | 10 in

 Length
 838.2 mm | 33 in

 Mounting Diameter, maximum
 127 mm | 5 in

 Mounting Diameter, minimum
 50.8 mm | 2 in

Stand-off Distance 914.4 mm | 36 in

Material Specifications

Material Type Hot dip galvanized steel

Mechanical Specifications

Wind Rating 120 mph (BWS) at 150 ft AGL | 140 mph (3-second gust) at 150 ft AGL using Exposure D per FBC

Wind Rating Test Method TIA/EIA-222

Packaging and Weights

Included Clamps | Stand-off

Packaging quantity 1

Weight, net 62.6 kg | 138.009 lb

ANDREW®
an Amphenol company

PB-G3T-2

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

* Footnotes

Warranty For more information, please consult our Product Warranty guidelines

Wind Rating BWS—Base Wind Speed; FBC—Florida Building Code

