

# F4A-HMDM-P-SGW

---

Base Product



HELIAX® 1/2" Superflexible SureFlex® Jumper with interface types 4.3-10 Male and 7-16 DIN Male with HELIAX® SureGuard weatherproofing

## Product Classification

|                       |                               |
|-----------------------|-------------------------------|
| <b>Product Type</b>   | SureFlex® Premium, static PIM |
| <b>Product Brand</b>  | HELIAX®   SureFlex®           |
| <b>Product Series</b> | RSJ4-50                       |

## General Specifications

|   |                  |
|---|------------------|
| <b>Attachment, Connector A</b>            | Factory attached |
| <b>Attachment, Connector B</b>            | Factory attached |
| <b>Body Style, Connector A</b>            | Straight         |
| <b>Body Style, Connector B</b>            | Straight         |
| <b>Interface, Connector A</b>             | 4.3-10 Male      |
| <b>Interface, Connector B</b>             | 7-16 DIN Male    |
| <b>Specification Sheet Revision Level</b> | A                |

## Dimensions

|                     |        |
|---------------------|--------|
| <b>Nominal Size</b> | 1/2 in |
|---------------------|--------|

## Jumper Assembly Sample Label

# F4A-HMDM-P-SGW



## Environmental Specifications

### Immersion Test Method

Meets IEC 60529:2001, IP68 in mated condition

### Weatherproofing Method

HELIAX® SureGuard weatherproofing boot