

# MTC3914T3



G22 High Capacity Three-Sector Frame with Work Platform 10.5 ft face, includes Twelve 126 in pipes; For patents, see [www.cs-pat.com](http://www.cs-pat.com).

**OBSOLETE**

This product was discontinued on: July 29, 2022

## Product Classification

**Product Type** High capacity Tower sector frame

## General Specifications

**Application** 4G LTE antenna/radio mount

**Mounting** Angle 60°, 203.2 mm (8 in) | Straight or tapered legs up to 203.2 mm (8 in) OD

**Patent Number** Patent pending

**Pipe, quantity** 12

**Tower Taper** Non-tapered | Tapered

## Dimensions

**Height** 3,200.4 mm | 126 in

**Face Width** 3.2 m | 10.5 ft

**Width** 3,200.4 mm | 126 in

**Pipe Length** 3,200.4 mm | 126 in

**Face Support Pipe Diameter** 60.325 mm | 2.375 in

**Mounting Diameter, maximum** 218.44 mm | 8.6 in

**Mounting Diameter, minimum** 38.1 mm | 1.5 in

**Pipe Outer Diameter** 60.325 mm | 2.375 in

**Stand-off Distance** 1,193.8 mm | 47 in

## Material Specifications

**Material Type** Hot dip galvanized steel

## Mechanical Specifications

# MTC3914T3

---

Wind Rating	For Specifications, please contact your local ANDREW representative
Wind Rating Test Method	TIA/EIA-222-G

## Packaging and Weights

Included	Frame   Pipe mounts   Plain end pipes (12)   Platform   Stiff arm   Tower attachment
Packaging quantity	1
Weight, net	1,129.445 kg   2490 lb

## Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

## \* Footnotes

Wind Rating	BWS—Base Wind Speed; FBC—Florida Building Code
-------------	--